

1SS352-BL-AH

Silicon Epitaxial Planar Switching Diode

Features


- AEC-Q101 Qualified
- Low Forward Voltage
- Fast Reverse Recovery Time
- Small Total Capacitance
- Halogen and Antimony Free(HAF), RoHS compliant

Application

- Ultra high speed switching

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode




Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Maximum (Peak) Reverse Voltage	V_{RM}	85	V
Reverse Voltage	V_R	80	V
Average Rectified Forward Current	$I_{F(AV)}$	100	mA
Maximum (Peak) Forward Current	I_{FM}	200	mA
Surge Forward Current (10 ms)	I_{FSM}	1	A
Power Dissipation	P_{tot}	200	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 150	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Max.	Unit
Thermal Resistance from Junction to Ambient ¹⁾	$R_{\theta JA}$	625	$^\circ\text{C/W}$


¹⁾ Device mounted on FR-4 substrate PC board, with minimum recommended pad layout.



1SS352-BL-AH

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit
Reverse Breakdown Voltage at $I_R = 10 \mu\text{A}$	$V_{(BR)R}$	80	-	V
Forward Voltage at $I_F = 100 \text{mA}$	V_F	-	1.2	V
Reverse Current at $V_R = 30 \text{V}$ at $V_R = 80 \text{V}$	I_R	- -	0.1 0.5	μA
Total Capacitance at $V_R = 0 \text{V}$, $f = 1 \text{MHz}$	C_T	-	3	pF
Reverse Recovery Time at $I_F = 10 \text{mA}$, $I_{RR} = 0.1 * I_R$, $V_R = 6 \text{V}$, $R_L = 100 \Omega$	t_{rr}	-	4	ns



1SS352-BL-AH

Electrical Characteristics Curves

Fig 1. Power Derating Curve




Fig 2. Total Capacitance vs. Reverse Voltage




Fig 3. Reverse Current vs. Reverse Voltage






Fig 4. Forward Characteristics




1SS352-BL-AH

PACKAGE OUTLINE


Plastic surface mounted package; 2 leads

SOD-323(Bend Lead)



UNIT	A	A ₁	b _p	C	D	E	H _E	L _p	Q	P
mm	1.1 0.8	0.1 0	0.4 0.25	0.18 0.09	1.8 1.6	1.35 1.15	2.8 2.3	0.5 0.1	0.5 0.3	0.4 0.3

Recommended Soldering Footprint



Packing information

Package	Tape Width (mm)	Pitch		Reel Size		Per Reel Packing Quantity
		mm	inch	mm	inch	
SOD-323BL	8	4 ± 0.1	0.157 ± 0.004	178	7	3,000


Marking information

" W2 " = Part No.

" III " = Cathode line

" • " = HAF (Halogen and Antimony Free)

Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice. Semtech Electronics Limited makes no warranties, representations or warranties regarding the suitability of its products for any particular purpose, and does not accept any liability arising from the application or use of any product or circuit such as: Apply to medical, military, aircraft, space or life support equipment and expressly waive any and all liability, including but not limited to special, consequential or collateral damage.

