

# 1SS400

## Silicon Epitaxial Planar Switching Diode

### Features


- Extremely small surface mounting type
- High reliability

### Applications

- For high speed switching application

### PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode




### Absolute Maximum Ratings ( $T_a = 25\text{ }^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	$V_{RM}$	100	V
Reverse Voltage	$V_R$	100	V
Average Rectified Forward Current	$I_{F(AV)}$	100	mA
Peak Forward Current	$I_{FM}$	225	mA
Non-repetitive Peak Forward Surge Current (at $t = 1\text{ s}$ )	$I_{FSM}$	500	mA
Operating Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	- 55 to + 150	$^\circ\text{C}$

### Characteristics at $T_a = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit
Reverse Breakdown Voltage at $I_R = 100\text{ }\mu\text{A}$	$V_{(BR)R}$	100	-	V
Forward Voltage at $I_F = 100\text{ mA}$	$V_F$	-	1.2	V
Reverse Current at $V_R = 80\text{ V}$	$I_R$	-	0.1	$\mu\text{A}$
Capacitance Between Terminals at $V_R = 0.5\text{ V}$ , $f = 1\text{ MHz}$	$C_T$	-	3	pF
Reverse Recovery Time at $I_F = 10\text{ mA}$ , $I_{rr} = 0.1 \times I_R$ , $V_R = 6\text{ V}$ , $R_L = 100\text{ }\Omega$	$t_{rr}$	-	4	ns



# 1SS400

## Electrical Characteristics Curves

Fig 1. Reverse Current vs. Reverse Voltage




Fig 2. Forward Characteristics






Fig 3. Total Capacitance vs. Reverse Voltage




# 1SS400

## PACKAGE OUTLINE


Plastic surface mounted package

SOD-523



UNIT	A	b <sub>p</sub>	C	D	E	H <sub>E</sub>	V	∠
mm	0.70 0.60	0.4 0.3	0.135 0.100	1.25 1.15	0.85 0.75	1.7 1.5	0.1	5°

### Recommended Soldering Footprint



### Packing information


Package	Tape Width (mm)	Pitch		Reel Size		Per Reel Packing Quantity
		mm	inch	mm	inch	
SOD-523	8	4 ± 0.1	0.157 ± 0.004	178	7	4,000

### Marking information

" A " = Part No.

" III " = Cathode line

Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice. Semtech Electronics Limited makes no warranties, representations or warranties regarding the suitability of its products for any particular purpose, and does not accept any liability arising from the application or use of any product or circuit such as: Apply to medical, military, aircraft, space or life support equipment and expressly waive any and all liability, including but not limited to special, consequential or collateral damage.

