

# SDB3480HC


## Surface Mount Schottky Barrier Rectifier

Reverse Voltage - 40 V

Forward Current - 3 A

### PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



### Features

- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability


### Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbols	Value	Unit
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	40	V
Maximum DC Blocking Voltage	$V_{DC}$	40	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	3	A
Peak Forward Surge Current 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	$I_{FSM}$	80	A
Operating Junction Temperature Range	$T_j$	- 55 to + 125	°C
Storage Temperature Range	$T_{stg}$	- 55 to + 150	°C

### Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit
Reverse Breakdown Voltage at $I_R = 100 \mu\text{A}$	$V_{(BR)R}$	40	-	V
Forward Voltage at $I_F = 3 \text{ A}$	$V_F$	-	0.55	V
Reverse Current at $V_R = 40 \text{ V}$ at $V_R = 40 \text{ V}, T_J = 100^\circ\text{C}$	$I_R$	-	0.05 20	mA



## Electrical Characteristics Curves

Fig 1. Average Rectified Current Derating Curve




Fig 2. Forward Characteristics Curve




Fig 3. Reverse Characteristics Curve






Fig 4. Junction Capacitance




# SDB3480HC

## PACKAGE OUTLINE


Plastic surface mounted package; 2 leads

SOD-123HE



UNIT	A	C	D	E	F	G1	G2	H <sub>E</sub>
mm	1.08	0.2	2.9	1.9	1.1	2.3	0.75	3.9
	0.88	0.1	2.6	1.7	0.8	1.9	0.55	3.5

## Recommended Soldering Footprint



## Packing information

Package	Tape Width (mm)	Pitch		Reel Size		Per Reel Packing Quantity
		mm	inch	mm	inch	
SOD-123HE	8	4 ± 0.1	0.157 ± 0.004	178	7	3,000

## Marking information

" DT1 " = Part No.  
 " III " = Cathode line  
 Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice. Semtech Electronics Limited makes no warranties, representations or warranties regarding the suitability of its products for any particular purpose, and does not accept any liability arising from the application or use of any product or circuit such as: Apply to medical, military, aircraft, space or life support equipment and expressly waive any and all liability, including but not limited to special, consequential or collateral damage.

