

TD01F20 THRU TD10F20

Surface Mount Fast Recovery Bridge Rectifier
Reverse Voltage - 100 to 1000 V
Forward Current - 2 A

Features


- Glass Passivated Chip Junction
- High Surge Current Capability

Mechanical Data

- Package: ABF
- Terminals: Solderable per MIL-STD-750, Method 2026

PINNING

PIN	DESCRIPTION
1	Input Pin (~)
2	Input Pin (~)
3	Output Anode (+)
4	Output Cathode (-)



Maximum Ratings and Electrical characteristics


Single-phase, half-wave, 60 Hz, resistive or inductive load rating at 25°C, unless otherwise specified, for capacitive load, derate current by 20 %.

Parameter	Symbols	TD01F20	TD02F20	TD04F20	TD06F20	TD08F20	TD10F20	Units
	Marking	ABF201	ABF202	ABF204	ABF206	ABF208	ABF210	-
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	100	200	400	600	800	1000	V
Average Forward Current $T_a = 100^\circ\text{C}$	$I_{F(AV)}$	2						A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	50						A
Maximum Instantaneous Forward Voltage at 2 A	V_F	1.3						V
Maximum DC Reverse Current at Rated DC Blocking Voltage $T_a = 25^\circ\text{C}$ $T_a = 125^\circ\text{C}$	I_R	1 100						μA
Typical Junction Capacitance ¹⁾	C_j	30						pF
Typical Thermal Resistance ²⁾	$R_{\theta JA}$ $R_{\theta JL}$	65 16						$^\circ\text{C/W}$
Maximum Reverse Recovery Time ³⁾	t_{rr}	500						ns
Operating and Storage Temperature Range	T_j, T_{stg}	- 55 to + 150						$^\circ\text{C}$

¹⁾ Measured at 1 MHz and applied reverse voltage of 4 V D.C.


²⁾ Mounted on glass epoxy PC board with 4x1.5"x1.5" (3.81x3.81 cm) copper pad.

³⁾ Measured with $I_F = 0.5\text{ A}$, $I_R = 1\text{ A}$, $I_{rr} = 0.25\text{ A}$.




TD01F20 THRU TD10F20


Average Rectified Output Current Derating Curve




Typical Reverse Characteristics





Typical Instantaneous Forward Characteristics



Typical Junction Capacitance



Maximum Non-Repetitive Peak Forward Surge Current




TD01F20 THRU TD10F20

PACKAGE OUTLINE

ABF

Plastic surface mounted package; 4 leads



UNIT	A	C	D	E	HE	d	e	L	L1	a	∠
mm	1.2	0.22	5.2	4.5	6.4	4.2	0.7	0.95	0.6	0.1	7°
	1	0.15	4.9	4.2	6	3.6	0.5				

Recommended Soldering Footprint

